



A Type	B Type
ELQ 250 E2 01 120901	ELQ 280 E2 01 120902
230V ~ 50 Hz 71/78/51 db(A) 1700 m³/h	230V ~ 50 Hz 75/79/53 db(A) 2300 m³/h
1,0 A 183 W 48 %	1,8 A 290 W 53 %
127818 B 600 H 600	127818 B 600 H 600
40,6 kg V	42,5 kg V

C Type	D Type
ELQ 315 E2 01 120905	ELQ 355 E2 01 120907
230V ~ 50 Hz 78/82/55 db(A) 3310 m³/h	230V ~ 50 Hz 79/83/61 db(A) 4830 m³/h
3,0 A 510 W 50 %	5,1 A 990 W 49 %
127818 B 600 H 600	127818 B 600 H 600
48,7 kg V	50,9 kg V

- High efficiency ETALINE diagonal fans
- Variable outlet and inlet configuration (on the right/left)
- High quality, thermal insulation, 40 mm
- Easy to maintain

--	--	--	--	--

- Step transformer
- 5-Step Transformer
- 5-Step Transformer
- Isolator Switch
- Fast clamps
- Back Draught Shutter
- Back Draught Shutter with seal
- Protection Grille Inlet
- Duct Silencer, rigid
- Duct Silencer, flexible

TES 0145 111858	TES 035 103954	TES 035 103954	TES 075 103957
TEE 015 115893			
	TEM 035 103502	TEM 035 103502	TEM 075 103507
GS 01 102787	GS 01 102787	GS 01 102787	GS 01 102787
VM 250 102651	VM 280 115494	VM 315 102652	VM 355 102653
RSK 250 102686		RSK 315 102664	RSK 355 102665
RSK 250D 113488		RSK 315D 113489	RSK 355D 113491
SG 250 02 112677	SG 280 02 115066	SG 315 02 112675	SG 355 02 112674
SDS 250 102721	SDS 280 115243	SDS 315 102723	SDS 355 102725
SDF 250 102705		SDF 315 102706	SDF 355 102707